# Height of the secondary distribution box foundation on site



## Overview

Height is 101.50 inches (2578.1 mm) for 27 kV MVS switchgear without fuses or with Cooper type NX fuses, and 38 kV MVS switchgear without fuses or with GE type EJO-1 fuses.

## Key Takeaways

The recommended height for a secondary distribution box foundation is typically 4. 5 to 5. 5 feet (1.

4 to 1. 7 meters) for wall-mounted boxes, with outdoor boxes at least 3 feet above ground. Recommended Installation HeightsWall-mounted distribution boxes: Mount at 4.

5 to 5. 5 feet (1. 4–1.

7 meters) from the floor to ensure easy access without bending or stretching, facilitating maintenance and emergency operations while complying with safety standards such as BS 7671 and IEC 60364-5-52. Outdoor boxes: Place at minimum 3 feet (0. 9 meters) above ground to protect against water, dirt, and accidental impacts.

Ground-mounted boxes: Raise 2 to 4 inches (5–10 cm) above the foundation to prevent moisture damage and ensure stability.



© 2026 ENSAA OPTICAL NETWORKS - All rights reserved

### Foundation and Site Considerations

The foundation should provide a level, dry, and maintenance-free area for the box, taking advantage of natural drainage and topography to avoid water accumulation. For substations or larger secondary distribution units, the foundation height may be coordinated with the overall yard grading to maintain uniformity in structure elevations and electrical clearances. Avoid placing the box over sewerage systems or water tanks; if unavoidable, maintain the standard height and trench depth as per construction drawings.

### Safety and Accessibility

Ensure the box is easily reachable for reading labels, performing inspections, and conducting repairs without strain. Keep the box away from wet areas and potential hazards to prevent electrical faults and physical damage. Use licensed electricians for installation to comply with local regulations and safety standards.

By following these height guidelines and foundation considerations, secondary distribution boxes can be installed safely, remain accessible for maintenance, and are protected from environmental and operational risks.

## Article Content

Secondary unit substations design guide

Height is 101.50 inches (2578.1 mm) for 27 kV MVS switchgear without fuses or with Cooper type NX fuses, and 38 kV MVS switchgear without fuses or with GE type EJO-1 fuses.

Secondary Substation Civil Design Guide

This standard details the civil design requirements for UK Power Networks'' secondary substations. It includes specific requirements for glass reinforced plastic (GRP) enclosures, brick-built, integral and

Substations

It permits uniformity in foundation elevations and structure heights. Unless there are property restrictions, severe topographical features, subterranean rock, or other considerations dictate

GENERAL SPECIFICATION FOR THE CIVIL SUB-03-017

As far as is reasonably practicable, this Specification shall also apply to works at existing SPEN substation sites, however; this will be determined on a site-specific basis by agreement with ED&S,

Secondary Substation Design: FAQ

*© 2026 ENSAA OPTICAL NETWORKS - All rights reserved*

When designing a substation with high level cable entry a minimum of 1500 x 1500mm clear floor area shall be provided to create a clear space locally where a scaffold tower can be safely erected to

Substations – Volume II

The high-profile, box-type structure arrangement shown in Figure 12 can accommodate multiple circuits in a relatively small area. The configuration is particularly suitable in environmentally shielded or

Secondary Distribution Substations

Third party retains ownership of the substation. SSEN designs and installs the substation. 1.2 This document covers secondary distribution substations with high voltage operating voltages of...

SDCS-02 CONSTRUCTION STANDARD FOR

TE: November 2016G Introduction This construction standard specifies the construction design of 13.8 & 33 KV Metered Ri.

SubstationDesign_2014-2015_Final_DP

THE DESIGN, TESTING, AND APPLICATION OF LIQUID-IMMERSED DISTRIBUTION, POWER, AND REGULATING TRANSFORMERS USING HIGH-TEMPERATURE INSULATION

SERVICE INSTALLATION SPECIFICATIONS AND DRAWINGS

The purpose of this procedure is to provide standards for the installation of underground electric secondary and communication conduit in general power applications.

What is the installation height of distribution box?

The outdoor distribution box should be firmly installed on the bracket or foundation. The height of the bottom of the box should not be less than 1.0m from the ground, and measures should

Key Points Of Installation And Collocation Of Distribution Box In ...

If they are combined in the same distribution box, power and lighting lines should be set separately. 7. The wire inlets and outlets in the distribution box and switch box shall be set at the lower bottom of

Critical Installation Considerations for Drop and Distribution Boxes

It is absolutely critical that d-boxes be installed level because they are used on level (or nearly level) sites. While absolutely equal distribution of flow with a distribution box is difficult to

*© 2026 ENSAA OPTICAL NETWORKS - All rights reserved*

Installing a Septic Distribution Box: D-Box Setup | Onsite Installer

Drop boxes are used to deliver effluent between trenches on sloping sites through sequential distribution. Basic definitions Distribution boxes are constructed with an inlet at the highest

Secondary unit substations design guide

Secondary unit substations requiring a primary disconnect are furnished with Eaton''s Type MVS metal-enclosed load interrupter switchgear assemblies. Each assembly consists of one

Primary and secondary power distribution systems (layouts explained)

Primary distribution systems Primary distribution systems consist of feeders that deliver power from distribution substations to distribution transformers. A feeder usually begins with a feeder

secondary distribution box,Class IIdistribution box-Ayump Electric

Power Distribution Box 1□ Classification The technical code for safety of temporary electricity on construction site (JGJ46-2005) clearly stipulates that the electricity on construction site must be three

Substations

Volume VIII, Site and Foundation Design. Covers general issues related to site design, foundation design and control house design. Volume IX, Substation Structures. Covers the design of bus

## Contact Us

Continue your research online:

Website: https://ensaa.es
Technical inquiry: https://ensaa.es/contact.html

This document is for preliminary research. Verify specifications against current standards, product documentation and project requirements.

© 2026 ENSAA OPTICAL NETWORKS - All rights reserved